

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 January 2004 (22.01.2004)

PCT

(10) International Publication Number
WO 2004/007853 A2


- (51) International Patent Classification⁷: **E03C 1/04**, F16B 43/00
- (21) International Application Number: PCT/GB2003/002992
- (22) International Filing Date: 11 July 2003 (11.07.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0216121.4 11 July 2002 (11.07.2002) GB
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant and
(72) Inventor: RYCROFT, Christopher [GB/GB]; 4 Manor Terrace, Queensway, Yeadon LS19 7NY (GB).
- (74) Agent: S J MOHUN; Haseltine Lake, West Riding House, 67 Albion Street, Leeds LS1 5AA (GB).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: WASHER



(57) Abstract: A splittable washer shown generally at (10), for example for use in a plumbing installation in which a pipe member is mounted in or connected to an article of sanitaryware, comprises separable parts (18) and (20) which are held together by hinge (16). When the washer is in the open configuration it may be fitted to or removed from the stem of tap on the underside of a sanitaryware unit without having to remove a securing nut from the stem of a tap. To close a washer the parts (18) and (20) are urged together until key projection (22) locates in socket (24). In the closed configuration the washer substantially encloses the stem of a tap.

WO 2004/007853 A2